



specification:	
Model:	IK02- ERL1-2812V
DSP	Hi3516C V200
Sensor	1/ 2.8 " CMOS (SONY IMX323)
video encode standard	H.264 HighProfile/MainProfile/BaseLine Profile/MJPEG /MJPEG/
Maximum image resolution	main stream: 1920 *1080 @25/ 30 fps
Video bitrate	32 Kbps~8MKbps
minimum illumination	color: 0.01Lux@F1.2 0.01Lux@F1.2 0.01Lux@F1.20.01Lux@F1.2 (AGC ONAGC ON AGC ON) ; balck and white: 0.001Lux@F1.2 0.001Lux@F1.2 0.001Lux@F1.20.001Lux@F1.2 (AGC ONAGC ON AGC ON)
D&N	AUTO/BLACK AND WHITE/COLOR(WITH IR CUT)
Lowest illumination	0.01LUX
DNR	SUPPORT 2D/3D DNR
Auto electronic shutter(AES)	AUTO(1/25-1/10000)
WDR	SUPPORT
Video Adjustments	Sharpness/contrast/brightness/saturation can be adjusted
Corridor pattern	SUPPORT

penetrating fog	SUPPORT
working voltage	DC12V/77mA \pm 6mA (wide voltage:9V-18V)
working temperature	-20°C --- 50°C