

SIMPLEBUS STYLE INTERCOM HANDSET

Entry phone with electronic call, conversation button on base, call volume control, privacy function, and conversation privacy. Equipped with a series of key buttons and a further 8 buttons for intercom function or various services (2 of the buttons can be used as a C/N.O contact). Equipped with LED that may be used for various signals (busy, doctor function). Complete with 8-position dip switch for selection of the desired user code. Door entry phone for use in all Simplebus systems. Allows management of floor door call, call repeat, sending of alarm signals to the porter switchboard, call to main switchboard, secondary switchboard and guardian door entry-phone. Allows direct intercom calls between users with the use of an interface or porter switchboard and the use of a number of relay actuators; programming of buttons does not require dedicated programmers. Fitted with terminal art. 1214/2C. The fascia can be changed on this model. Dimensions: 95x215x58 mm.



General specifications

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
B/W or colour display:	-
Product colour:	White RAL9003, cover light blue
Interchangeable cover:	Yes
Sensitive Touch technology:	No
Total buttons:	9
LED signaling (No.):	1
Backlighting color:	-

Functions

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call to group addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Doctor:	Yes

DATA SHEET

Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Mechanical ringtone:	No
Customisable ringtone:	Yes
Alarm function:	No
Privacy conversation function:	Yes
Key button function:	Yes

Hardware specifications

Customisable housing:	Yes
-----------------------	-----

Settings

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes

General data

Product height (mm):	215
Product width (mm):	95
Product depth (mm):	58

Compatibility

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

Technical specifications

Power supply voltage:	22 ÷ 28
Absorption:	1
Maximum current absorption (mA):	200
Microphone:	9,6x6,9mm omni-direction
Loudspeaker:	
IP Rating:	IP30
Operating temperature (°C):	-5 ÷ 40
Product weight (g):	0,55
Clamps:	L L CFP CFP LED+LED- SS+C8 P8 C9 P9