### **DATA SHEET**

# **COD. 2738W**

# DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS TOP A/V. MINI SER.

MINI series door-entry phone for SBTOP system with electronic call, key button and additional button for extra services (switchboard call, actuator and generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Door-entry phone for use in mixed audio/video SBTOP systems. Fitted with terminal art. 1214/2C. Dimensions: 105x191x28



#### **General specifications**

System:	SimplebusTop (S1 e S2)
Audio system:	Yes
Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	_
Induction loop function:	-
Product color:	Bianco
Total buttons:	2
LED signaling:	No

#### **Functions**

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	-
Intercom function:	-
Selective intercom call:	-
Privacy function:	Yes
Doctor:	-
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	-
Key button function:	Yes

#### Settings

Loudspeaker volume control:	Yes



### **DATA SHEET**

Micr	rophone volume control:	No
Ring	gtone volume control:	Yes
General info		
Prod	duct height (mm):	190
Prod	duct width (mm):	103
Prod	duct depth (mm):	30
Technical sp	pecifications	
Sup	ply voltage:	22÷35 Vdc
Pow	ver consumption stand-by (mA):	0,5÷0,710 Vdc
In ca	alled absorption (mA):	25÷30 mA
In co	ommunication absorption (mA):	23÷30 mA
Micr	rophone:	Ø 9,6 x 6,9 mm
Spe	aker:	Ø 0,50 mm ; Max Imput Power 0,5W
IP R	Rating:	30
Ope	erating temperature (°C):	-5÷40
Prod	duct weight (g):	0,257 Kg
Clar	mps:	L,L,CFP,CFP

