

RFID Reader

Vandal-proof 13.56 MHz Contactless Reader



- Wiegand 26/34 or RS485 Protocol
- MIFARE 13.56 MHz Card
- Watch Dog Function for Tamper Detection
- Metal Keypad Buttons with Blue Backlight
- Audible and Visual Indicators
- Surface-mount Installation



Technical Specification

System

Main Processor	8-bit
LCD Display	Red and Green LED Indicators, Blue Backlight
Audible Indicator	Buzzer

Reader

Format	13.56 MHz MIFARE
Distance	6.0 cm to 8.0 cm (2.36 in. to 3.15 in.), maximum
Response Time	< 0.1 s
Keypad	Metal Button Keypad 12 Keys (1 to 9, *, #), Key 5 has Braille Markings

Interface

To Controller	Wiegand 26/34 or RS485
---------------	------------------------

Certifications

Safety	EN 60950-1:2006+A11:2009+A1:2010+A12:2001+A2:2013 Conforms to UL Standards
Electromagnetic Compatibility (EMC)	FCC CFR 47 Part 15 subpart B EN 55032:2015 EN 55024:2010+A1:2015 EN 50130-4:2011+A1:2014 EN 6100-3-2:2014, EN 6100-3-3:2013

Electrical/Environmental

Power Supply	9 VDC to 15 VDC, 100 mA
Operating Temperature	-30° C to +60° C (-22° F to +140° F)
Operating Humidity	≤ 95%
Vandal Resistance	IK08

Construction

Color	Black
Dimensions	110.10 mm x 85.20 mm x 26.0 mm (4.33 in. x 3.35 in. x 1.02 in.)
Net Weight	0.50 kg (1.10 lb)

Accessory - IC Card

Model Number	MF11CS50
Standard	MIFARE S50, 13.56 MHz
Compatibility	ISO/IEC 14443A
Range	Approximately 10 cm (3.94 in.)
Dimensions	86.0 mm x 54.0 mm x 0.80 mm (3.39 in. x 2.13 in. x 0.03 in.)
Weight	0.006 kg (0.013 lb)
Manufacturer/Brand	Dahua

Dimensions (mm/in.)

