

# LM49-S400

## 49" UHD LED Monitor



### Features:

- Industrial level LCD panel, suitable for continuous 24/7 operation
- 4K Ultra-HD resolution
- Using tamper-proof metal housing
- Built-in 3D COMB filter and 3D noise reduction
- 8ms response time for no motion blur, judder or ghosting
- 1.07G colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° extra-wide viewing angle for overall viewing performance
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption
- Support multiple signals, such as HDMI, DP, VGA, USB multimedia, Audio, RS232



### Technical Specification

#### Model

Model	LM49-S400
-------	-----------

#### Display

Screen Size	49"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/㎡
Contrast Ratio	1000:1
Display Color	1.07G(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

#### Signals

Input	DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

#### General

Power Supply	AC110~240V , 50/60 Hz
--------------	-----------------------

Consumption (Standard)	<90W	
Type	Internal	
Net Weight	20.5kg (45.2lb)	
Gross Weight	30.5kg (67.2lb)	
Bezel Width	8mm (U/L/R/B)	
VESA	400×400mm (15.7"×15.7")	
Dimension without base (W×H×D)	1091.5×623.2×65.0mm (43.0"×24.5"×2.6")	
Package(W×H×D)	1275×795×255mm (50.2"×31.3"×10.0")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

#### Accessory

Standard	HDMI cable, power cable, hanging bracket, remote control
Optional	Pedestal

#### Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

