

BioCam 300

Embedded Face Recognition IP Camera



Description

Biocam300 is an embedded facial recognition high definition IP camera, with 4pcs of array IR LEDs, it can realize day & night real-time monitoring. Adopts ZK embedded high integrated facial recognition module and relatively long distance face recognition algorithm, it can support 1.5m to 2.5m range facial recognition suitable for different users' heights. BioCam300, with remote control, has a high definition full color display screen to show face registering information, face recognition result and real-time monitoring video. The operation is very simple and the interface is user friendly.

With dual CPU framework, camera can accomplish register, recognition and storage standalone to keep high speed data transmission. It can support 400 faces registration and recognition while real-time monitoring. Biocam300 is a three-in-one solution including video surveillance, time & attendance and single channel access control management. It can be applied in many higher security areas such custom, airport, building, bank, supermarket, hotel, gambling house, VIP club, turn style, parking lots and etc.





Key Features

High resolution

Biocam300 support 1 megapixel resolution, suitable for all kinds of environments under all light conditions.



7 inch HD LCD for information display

With high definition LCD to show face registering information, face recognition result and real-time monitoring video, it will bring nice experience for users.

8:57 Fir





02.17


Remote control for easy operation

All the functional operations are performed via the remotecontrol including face registering and recognition. It has excellence user experience.



Latest long distance facial recognition a gorithm

Adopts newest version of ZK long distance face recognition algorithm, Biocam300 can support 2.5m to 4m range facial recognition suitable for different users' heights



Time & attendance function is supported

Biocam300 can support 400 faces registration and recognition and 100,000 logs for standalone time and attendance function, it is suitable for many difference application areas such as office, supermarket, chain store, enterprise and etc.



Single channel access control management

With face recognition technology, the Biocam300 has relay output for direct electric lock control. It can be applied in variously higher security environments such as government, bank, custom, VIP club, gambling house, turn style and etc.





Technical Specification

Model BioCam 300

Product Name Embedded face recognition IP camera

Camera Performance

Image Sensor 1/3" WDR progressive CMOS

Image Resolution 1280×720

Minimum Illumination 0.5 Lux (IR off), 0 Lux (IR on)
Day & Night Automatically IR-cut filter
SNR ≥60db(AGC OFF, Weight On)

Lens 4 mm fixed lens

IR Distance : 5~7 m; 84° project angle

Face Recognition

Face Capacity 400 Verification Speed ≤ 1s

Template Capacity 12 template /Face

Logs Capacity 100,000
Camera Display 7 inch LCD

Audio Output 1 channel line output

Video

OS Embedded Linux

Video Compression H.264 main profile level 3
Video Resolution Main Stream: 1280x720
Second Stream: 352 x288

22K~10240kb--

Code Stream 32K~10240kbps
Frame Rate NTSC: 1~30; PAL: 1~25

Image Setting Brightness , saturation, contrast,

chroma, gain, flip vertically/horizontally

Function & Port

Control Remote Control

Time and Attendance Yes

Access Control Simple access control function (door sensor,

exit button, 3rd party electric lock, wiegand input)

Communication TCP/I

Motion Detection Independent detection areas settable

Storage Support TF card, up to 32G

Network Interface 10Base-T/100Base-TX Ethernet interface

Supported Protocol TCP/IP, HTTP, UDP, ARP, SMTP, FTP, DHCP, DNS, DDNS, NTP,

UPNP, RTSP/RTCP/RTP,ONVIF

Working Conditions

Power Supply DC 12V / 1.5A


Power Consumption 13W


Working Temperature -10°C~50°C






Product Dimension







Application



Custom



Airport



Building



Bank



Supermarket



Hotel



Gambling house



VIP club



Turn style



Parking lots

