

KR610 Series



KR610



KR611



KR612

Specifications

	KR610				KR611				KR612			
	E	E-RS	D	D-RS	E	E-RS	D	D-RS	E	E-RS	D	D-RS
Proximity	EM 125 KHz		Desfire 13.56 MHz		EM 125 KHz		Desfire 13.56 MHz		EM 125 KHz		Desfire 13.56 MHz	
Read Range	Up to 10 cm		Up to 5 cm		Up to 10 cm		Up to 5 cm		Up to 8 cm		Up to 4.5 cm	
Reading Time	≤300ms											
Input Port	External LED Control / External Buzzer Control											
Material	ABS+PC with texture											
Output Format	26/34 bits	26 bits	34/66 bits	66 bits	26/34 bits	26 bits	34/66 bits	66 bits	26/34 bits	26 bits	34/66 bits	66 bits
Power/Current	DC 6-14V / Max.70mA											
LED	Red and Green LEDs											
Operating Temperature	-20°C to 65°C(-10° to +70°C)											
Operating Humidity	10% to 90% relative humidity non-condensing											
Beeper	Yes											
Index of Protection	IP65								IP64			
Dimensions	75x116x16 mm				86x86x16 mm				86x86x20 mm			
Cable length	Standard 35 cm (Optional 150 cm)											