

# Triple PB-150D2



<b>Model</b>	<b>Triple PB-150D2</b>
<b>Outdoor Range</b>	150m
<b>Indoor Range</b>	450m
<b>Detection Method</b>	Simultaneous interruption of 3 infrared beams
<b>Interruption Time</b>	50ms,100ms,300ms,700ms (selectable)
<b>Frequencies</b>	4 different channels selectable
<b>Power Supply</b>	DC/AC 12~24V
<b>Max Current</b>	90mA
<b>Alarm Period</b>	2sec (±1)
<b>Alarm Output</b>	1C. relay output (AC/DC30V, 1.0A max)
<b>Tamper Switch</b>	NC, opens when cover removed
<b>Protection Degree</b>	IP65
<b>Operating Temperature</b>	-25°C to +55°C
<b>Environment Humidity</b>	95% max
<b>Alignment Angle</b>	Horizontal 180°(±90°), Vertical 20°(±10°)
<b>Mounting</b>	Outdoor or indoor, Wall or Pole
<b>Material</b>	PC engineering plastic
<b>Dimension (L*W*H)</b>	90mm*100mm*270mm
<b>Weight (TX and RX)</b>	1900g

Note: When environment temperature lower than -20°C, please use heaters to ensure normal working. Heater is non-polarized.