

# NF-2S

In order to ensure the greatest possible health protection for the employees, glass partitions are set up for direct customer contact at many reception desks, ticket counters, gatehouses, hotel receptions, concert box offices or patient receptions in surgeries.

So, 2 people wearing masks speak through this glass partition and no one understands the other. What can be done?

Thanks to full-duplex support, TOA's NF-2S window intercom system provides a natural, easy-to-understand, and high-quality two-way communication. With powerful DSP for echo and noise cancellation, the NF-2S system is an all-in-one solution with easy set-up, even for end users without technical expertise. The flexible system is customisable for the operator using a headset.

---



Article number:NF-2S 1CE

---

## Specifications

|                       |  |
|-----------------------|--|
| Indicator             | Power indicator LED, Signal indicator LED  |
| Audio input           | Base Unit: mic input, -30 dB, 3.5 mm mini jack (4P), phantom power supply  |
| Audio output          | Base Unit: 16 Ω, 3.5 mm mini jack (4P)   |
| Power source          | 100 - 240 V AC, 50 / 60 Hz (use of the supplied AC adapter)  |
| Rated output          | 1.7 W  |
| Control input         | Base Unit:<br>External mute input: No-voltage contact inputs<br>Open voltage: 9 V DC or less, short-circuit current: 5 mA or less<br>Push-in terminal block (2 pins) |
| Current consumption   | 0.2 A  |
| S/N ratio             | 73 dB or more (volume: min.)<br>70 db or more (volume: max.)   |
| Finish                | Base Unit:<br>Case: ABS resin, white, paint<br>Panel: ABS resin, black, paint<br>Sub-Unit: ABS resin, white, paint   |
| Operating humidity    | 85 %RH or less (no condensation)   |
| Operating temperature | 0 °C to +40 °C   |



---

Appearance