

NX-100

NETWORK AUDIO ADAPTER

The NX-100 Network Audio Adapter can transmit high-quality audio signals and such control data as serial data over IP networks, such as LAN or Internet, in real time. It is especially useful when transmitting audio signals to remote locations, as Internet use keeps running costs lower than the use of dedicated lines. With the use of an optional rack mounting bracket, it can be mounted in an EIA Standard rack (1 unit size).



Order no: NX-100 W

Specifications

Power source	24 V DC
Power consumption	4,89 W (DC operation)
Control input	8 (no-voltage make contact) (12 V DC, 10 mA)
Control output	8 (open collector, 30 V DC, 50 mA)
Network	10BASE-T/100BASE-TX, Auto-negotiation
Audio input	1 channel (isolated transformer), -58 dBV to 0 dBV, balanced (MIC/LINE changeable, volume adjustable with volume control), 2 k Ω , removable terminal block
Audio output	1 channel (isolated transformer), balanced, 600 Ω , removable terminal block 3-pins
Dimensions (W x H x D)	210 x 46 x 188 mm
Dimensions (ϕ x D)	x 188 mm
Finish	Steel plate, paint, black
Operating humidity	Under 90 % RH (no dew condensation should be produced)
Operating temperature	0°C to +50°C (0°C to +40°C when AC adapter is in use)

NX-100

NETWORK AUDIO ADAPTER

Appearance

