

The unit provides 9 buttons for any assignable PA function and 8 volume controls that can be assigned to any audio input or output of the VX-3000 system.



Article number:VX-3000CT

Specifications

Controls	9 push buttons for assignable PA functions,8 volume controls (rotary knobs) for any assignable audio inputs or outputs
Indicator	POWER (green) ... 1, RUN (green) ... 1, LINK/ACT (green) ... 2,SIGNAL (green) ... 8, FAULT (yellow) ... 1, STATUS (green/yellow) ... 9,SELECT (green) ... 9
Power source	20 - 33 VDC
Indicator	POWER (green) ... 1, RUN (green) ... 1, LINK/ACT (green) ... 2,SIGNAL (green) ... 8, FAULT (yellow) ... 1, STATUS (green/yellow) ... 9,SELECT (green) ... 9
Power source	20 - 33 VDC
Connection	2 LAN ports (LAN A, LAN B)
Current consumption	0.09 A at 33 V DC input, 0.11 A at 24 V DC input
Connection	2 LAN ports (LAN A, LAN B)
Finish	Steel plate, 30% gloss, paint, black, Volume control section cover: ABS resin, gray smoke
Operating humidity	90% RH or less (no condensation)
Operating temperature	0°C - 40°C



VX-3000

VX-3000CT

Appearance