













Human Detector systems guard exhibits and pieces of art in collections and museums



Human Detector systems

guard and protect exhibits and pieces of art

The **Human Detector** system can be quickly installed and represents a powerful, compact security and monitoring system for the deployment in car show rooms, private collections and museums. It effectively protects works of art and exhibits from physical contact, theft or vandalism. The **Human Detector** reliably detects if a person touches the monitored object *2 and controls monitoring cameras as well as alarm systems. Our **Human Detector** technology can be implemented into existing systems.

The **Human Detector** offers unique protection for mobile cultural assets. The compact modules can be installed on exhibits within minutes. Alert messages are transmitted via radio for distances of up to 300 metres, irrespective of the location of the monitored exhibit. *3. The **Human Detector** does not need any networking or a separate power supply. Integrated batteries or an external power supply allow for long term operation. The **Human Detector** features three physical sensor systems, working independently from each other. The capacitive sensor monitors the outer layer of the object to be protected. The device reliably detects physical contact of surfaces and exhibits at an early stage. *2.

The seismic sensor detects the slightest vibration of the object to be monitored. Physical contact with any objects, such as tapping of walking sticks or opening of doors and flaps in antique furniture are reliably detected. The optional radar sensor monitors the area around the exhibit. Anyone reaching into the monitored area is detected. In addition the **Human Detector** features a port for the connection of various alarm sensors, such as pressure and motion sensors.


The **Human Detector** provides comprehensive protection for vehicles in car dealerships and collections. Its deployment is cost-effective, fast and flexible. Damages through theft, vandalism and carelessness are sustainably reduced.

Please also refer to the following information:

Human Detector - Protection of automobiles **Human Detector** - Sale Support



These are found under www.human-detector.com





Small Collections and Exhibitions

... are protected with the **Human Detector** in a simple and fast manner. An acoustic alarm is triggered, if a visitor touches an exhibit. The intensity of the sound can be adjusted. The alarm signal can be transferred onto a video surveillance or alarm system if required. A signal in a central location is therefore made possible.

The **Human Detector** provides first class protection against theft, vandalism and unintentional damage. The system is best deployed for the protection of pictures, statues, sculptures, display cabinets, furniture, and mechanical exhibits as part of small collections and exhibitions. The fast and simple installation of the **Human Detector** module enables the quick adaptation to changes within the exhibition.





Exhibitions in Museums

... can be protected with the **Human Detector** in a sustainable manner. For this purpose a **Human Detector** is installed on the object to be protected. If required, an acoustic alarm is triggered when an exhibit is being touched, and the **Human Detector** centre is being informed via radio. If a visitor touches the object an acoustic alarm is triggered (which can be switched off) and the **Human Detector** centre is informed via radio. A video camera pans onto the exhibit and records the incidence, if required. In a museum, the **Human Detector** offers cost-effective protection against theft, vandalism and the well-known "gropers". The systems are equally suitable for permanent, as well as temporary exhibitions.

Private and Corporate Collections

... are protected against damages and theft by the **Human Detector**.

There has been an on-going trend to invest into art and collectibles. These "treasures" are in the possession of private individuals as well as corporations. Works of art are often exhibited in rooms, which are open for receptions or festivities. The likelihood of exhibits being damaged at such occasions is high.

The **Human Detector** modules can be places in concealed locations on the exhibit to be protected. If a guest enters the secured area, a discreet acoustic alarm is triggered. A video recording can be taken, if required. The **Human Detector** can be operated over a period of several months with the help of high-performance batteries. Networking via radio is possible at any time, even retroactively.



Complete protection

via multi-sensor technology

The surveillance of works of art and exhibits poses a complex task. The reason for this is the variety of objects and the desire to implement protection by using only one product.

The **Human Detector** comprises several sensors. These sensors provide for the nearly complete monitoring of exhibits in exhibitions and collections. Additional sensors can be added if necessary.

Capacitive Surface Sensor



The surface sensor detects human contact on metallic objects and surfaces. Even the slightest touch is reliably detected. Depending on the adjusted sensitivity, the approach is detected long before an object is touched. Pictures, statutes and sculptures, as well as technical objects, are therefore effectively protected.

Seismic Sensor




The vibration sensor measures the slightest vibration on the monitored object. These can occur when display cabinets are opened or parts of the monitored object are dismantled. The **Human Detector** is equipped with two independently working seismic sensors. Even the slightest vibration is therefore reliably detected.

Radar Sensor (optional)



The optional radar sensor monitors the area around the exhibit. Large volume exhibits could be protected on this way. The radar sensor is mounted in a separate enclosure and is connected by cable with the **Human Detector**.

External Sensor Connection



Additional alarm sensors can be connected to the **Human Detector**. Smoke detectors, door contacts, pressure alarm, motion and other sensors can therefore be incorporated.



Wide range of deployment options at a glance

Exhibit/object	Capacitive sensor	Seismic sensor	Radar sensor	Other sensors
Paintings and pictures	Sensor foil or plate behind image, protection against physical contact	Protection against mechanical damages, e.g. cutting		Combination with suspended sensor
Sculptures	Suitable for objects made of conductive material, such as bronze	Protection against tipping, impact damages, etc.	Protection of large-scale objects	
Display cabinets and showcases		Protection against mechanical damages and breaking in	Protection of the interior of large-scale display cabinets	Connection of door contacts, temperature- and climate control
Furniture	Sensor foil or wire in furniture, protection against physical contact	Protection against damage and opening of doors	Protection of large pieces of furniture, replaces barriers	
Models and relief maps	Protection against physical contact of surfaces, theft of small components	Protection against impact damages and dismantling	Protection of large-scale objects	
Exhibition platforms	Protection against entering, protection of pedestal edge	Protection against impact damages and storage of objects	Protection of large-scale pedestals	Connection of PIR-motion sensors
Figurines and animal dermoplastics	Protection against physical contact and theft of small components	Protection against tipping, impact damages, etc.		
Frescos and carvings	Protection against physical contact and damage to surface	Protection against mechanical damages and theft		
Sacral art	Protection against physical contact and damage	Protection against mechanical damages and breaking in	Protections of altars, cribs, etc.	Connection of PIR-motion sensors

Human Detector – Advantages at a glance:

- · Complete protection through multi-sensor surveillance
- \cdot Detects approaches before contact takes place
- · Acoustic alarm on the exhibited object for security staff
- · Ideal for permanent and temporary exhibitions
- · Worldwide access and alert via smartphone
- · Wireless network and voltage supply
- · Can be integrated with existing alarm / surveillance equipment
- · Control of movable surveillance cameras (PTZ)
- · Extensive surveillance due to a radio range of 300 metres *3
- · Straightforward installation of the **Human Detector** sensors
- · Security made in Germany








1 to max.1000 Human Detector sensors







Human Detector

a system growing with its tasks

The **Human Detector** can be operated in a range of different configuration stages. The possibilities range from the protection of individual objects with a local acoustic alarm to the protection of entire museums and collections. They can also be distributed over separate locations or several floors, if required.

Operation without Networking

The protection of objects and works of art from physical contact is often requested at exhibitions. It is often sufficient to sound a short warning signal. Careless visitors are warned and security staff are made aware of the situation. The **Human Detector** modules are mounted to the objects to be protected and are not networked via radio. The system can also be networked at a later stage.

Operation with Networking


The **Human Detector** modules are connected to the **Human Detector** centre via radio. It comprises a loud alarm siren, emergency power supply as well as ports for connecting external alarm- and surveillance devices. The radio transmission is of a high standard. Availability and condition of the batteries in the **Human Detector** modules are continuously monitored. Failure and attempted manipulation are therefore detected at an early stage.

The networked operation represents the ideal solution for deployment in collections and museums. The majority of visitors and interested parties are not disturbed by acoustic alarms at the individual exhibits. The recording of all alarm conditions and the subsequent processing of these is carried out at a central location. Security staff can be alerted in different ways. Recordings and configurations are carried out by a PC. Multilingual control software is included in the consignment.

Standardised Interfaces offer Flexibility for further Expansion


The **Human Detector** centre comprises 8 digital outputs and 1 NC-alarm output. Additional devices such as sirens, alarm systems, personal paging systems, surveillance cameras or telephone diallers can be connected.


Each **Human Detector** sensor is capable of triggering an individual alarm. Actions are triggered according to the level of threat. The alarms can be documented and recorded with the help of a computer.



Intelligent Deployment of Video Technology

The **Human Detector** centre controls up to 255 surveillance cameras and network recording devices from different manufacturers with the help of the acknowledged Pelco protocol. All unwanted actions, such as touching of statues, can therefore be recorded. Movable PTZ-cameras are precisely directed towards the required object. The monitoring and recording is carried out automatically and does not require additional staff.





data logging via

USB-interface

PIO- or NC-

Messages are send to smartphones and computers via optionally connected network recording devices. In the case of an alarm an alert is sent via e-mail or SMS. Video images can be checked from anywhere in the world to enable you to decide on the required course of action. The exhibits can be monitored via smartphone or computer at any time, irrespective of an alarm occurring.



The Human Detector system at a glance:





- · Integrated seismic and capacitive sensors (adjustable sensitivity)
- · Optional radar sensor for monitoring open spaces
- · Connection terminals for external alarm systems (such as motion sensors)
- · Isolated output NC (VDS compatible)
- · Long term operation with powerful lithium batteries
- · Integrated loud transmitter for alarm messages (adjustable duration)
- · Secure, encrypted radio operation with a range of up to 300 metres *3
- · Installation with screws, glue, ties or magnetic mounting plate
- · Measurements sensor housing: 117w x 85h x 41d in mm
- · Weight: 160 grams (including batteries)
- · Operating voltage: 2 x lithium CR123 batteries or via external power supply
- · Scope of delivery: Sensor module, 2 x CR123 batteries, installation instructions



Item: HD-C Human Detector centre

- · Centralized control for **Human Detector** module (max. 1000)
- · Secure, encrypted radio operation and large range through separate aerial *3
- · Embedded, powerful alarm siren
- · RS-485 interface for controlling of external surveillance cameras and recording devices (PELCO)
- \cdot 8 x alarm output for controlling video recording devices, sirens, signal lights, etc.
- · Installed rechargeable battery for emergency operation in case of power failure
- · USB-interface for configuration, including configuration software in German/English
- · Measurements housing for wall mounting: 139w x 210h x 58d in mm
- · Weight: 460 grams (without power supply)
- · Operating voltage: 230V/50 Hz AC
- · Scope of delivery: **Human Detector** centre, power supply, configuration software (Win), installation instructions



Item: RS-1Z Radar sensor

- · Single-zone radar sensor *4
- · Range: approx. 2.5m (adjustable)
- · Measurements housing: 68w x 60h x 14d in mm
- · Weight: 30 grams
- · Operating voltage: 12V DC (connector for **Human Detector**)

Recommended accessories:

· Replacement batteries for ltem: CR123

Human Detector

· 12V supply cable Item: HD-12V

Potential plate for loose installation
Connector cable with clips
Item: HD-GND
Item: HD-AS

· Magnetic mounting plate Item: HD-MAG

· PTZ-surveillance cameras on request

NVR-network video recording device on request
Alarm systems, sirens and accessories on request

· Paging systems on request

- *1 The capacitive sensor can only be deployed in a dry environment (indoor).
- *2 Capacitive sensors work with conducting materials, such as bronze, brass and steel.
- *3 The range is variable depending on the type of building and fittings Maximum distances can be achieved in open spaces.
- *4 The optional radar sensor has an independent housing, therefore increasing the total power consumption. For operation an external power supply (mains) is required.

Technical specifications are subject to change without notice.

© by heddier electronic GmbH.



Additional accessories are available on request. We would be very happy to provide advice for the integration of our Human Detector systems into your existing alarm- and video surveillance systems.

Distributed by: